

Pin Configuration for MSD800 /4 & /8

Page 1/1

DK-Audio A/S
 Marielundvej 37 D
 2730 Herlev, Denmark
info@dk-audio.com
www.dk-audio.com/

OUTPUT AUDIO & UTILITY CONNECTOR			
<i>9-Pole DSUB Female</i>			
Power & RS232:			
+ Vcc	12 - 15 V	Pin 4	
Power ground		Pin 5	
RS232	TX	Pin 2	
RS232	RX	Pin 3	
AES sync.	Signal	Pin 8	
	Signal	Pin 9	
	GND	Pin 1	
Output:			
Analogue Left	Hot	Pin 7	
	Cold	Pin 6	
	GND	Pin 1	
Analogue Right	Hot	Pin 9	
	Cold	Pin 8	
	GND	Pin 5	

INPUT AUDIO CONNECTOR			
<i>25-Pole DSUB Female</i>			
Power:			
+ Vcc	12 - 15 V	Pin 25	
Input:			
Analogue 1	Hot	Pin 14	
	Cold	Pin 1	
	GND	Pin 2	
Analogue 2	Hot	Pin 3	
	Cold	Pin 15	
	GND	Pin 16	
Analogue 3	Hot	Pin 17	
	Cold	Pin 4	
	GND	Pin 5	
Analogue 4	Hot	Pin 6	
	Cold	Pin 18	
	GND	Pin 19	
Analogue 5	Hot	Pin 20	
	Cold	Pin 7	
	GND	Pin 8	
Analogue 6	Hot	Pin 9	
	Cold	Pin 21	
	GND	Pin 22	
Analogue 7	Hot	Pin 23	
	Cold	Pin 10	
	GND	Pin 11	
Analogue 8	Hot	Pin 12	
	Cold	Pin 24	
	GND	Pin 13	